



LED Chip Brand



Specifications

Model No.	E017EI	E017EI	E017EI	E017EI	E017EI	E017EI	E017EI
Power Consumption(±10%)	20W	30W	50W	70W	100W	150W	200W
LEDs Type &Qty (SMD2835)	25pcs	36pcs	54pcs	81pcs	108pcs	162pcs	216pcs
Luminous Flux (±10%)	2000lm	3000lm	5000lm	7000lm	10000lm	15000lm	20000lm
Efficacy (±10%)	100LM/W						
Correlated Color	6500K (3000K, 4000K ,5000K optional)						
Color Rendering Index	Ra70 (Ra80 optional)						
Beam Angle	120°						
Power Supply	OUTLUX Linear DOB						
Frequency	50 / 60 Hz						
Input Voltage	220-240 VAC						
Range of Voltage ACCEPTABLE	180-265 VAC						
Power Factor	≥0.9						
Surge Protection	1KV	3kV					
Product Dimension (mm)	113×137×22	135×163×22	163×189×22	189×220×22	226×260×24	266×305×25	302×345×27
Luminaire Net Weight (Kg)	0.32	0.4	0.6	0.8	1.25	1.65	2.35
Pcs/Carton	40	30	20	10	10	6	5
Export Carton Size(cm)	33.5×24.6×30	43.5×33.5×18	34.6×33.5×21	30.5×20.5×24	33.5×24×28	28×21×32.5	33.2×19×38
Gross Weight (Kg)	9.9	11.7	11.4	8.7	14	11	12.9

Highlights :

- 1.Private mould with elegant design, OUTLUX patented product
- 2.Clean and elegant full glass design for simple return.
- 3.Angle bracket with 270°rotation,capable of quick and easy installation.
- 4.Respirator as standard to avoid vapour (30W ~200W).
- 5.Multiple light distribution to suit more different applications.

Material	Housing	Die casting aluminum
	Optics	Toughened glass
Finish	Powder Coating	
Fixture Color	Black/Gray	
IP Rating	IP65	
IK Rating	IK06	
Insulation class	Class I	
Mounting Option	Fixed installation	
Operating Temperature	-40°C to + 50°C	
Life Time	>36000Hrs (Ta=30°C@L70)	
Warranty	3 Years	
Power cord	SAA 3*1.0mm ² 150CM Australian regulation plug cable	