

# OUTLUX



## E023EIS STELLAR FLOODLIGHT

Model No.	E023EIS	E023EIS	E023EIS	E023EIS
Power Consumption(±10%)	10W	20W	30W	50W
LEDs Type &Qty (SMD2835)	13pcs	25pcs	36pcs	54pcs
Luminous Flux (±10%)	950lm	1900lm	3000lm	5000lm
Efficacy (±10% )	100LM/W			
Correlated Color	6500K (3000K, 4000K ,5000K optional)			
Color Rendering Index	Ra70			
Beam Angle	120°			
Power Supply	Unisolated constant current Drive			
Driver Type	Linear Constant Current (CC)			
Input Voltage	220-240 VAC			
Range of Voltage ACCEPTABLE	185-265 VAC			
Power Factor	≥0.9			
Frequency	50 / 60 Hz			
Surge Protection	1kV	1kV	2kV	2kV
Product Dimension (mm)	108×123×43	143×147×43	174×171×43	207×193×43
Luminaire Net Weight	0.2Kg	0.29Kg	0.4Kg	0.56Kg
Pcs/Carton	40pcs	20pcs	20pcs	10pcs
Export Carton Size(cm)	47.2×26×27.4c	31.2×25.5×31.4	36.8×25.5×36.8	40.6×25×22.7c
Gross Weight	9.4Kg	6.8Kg	9.1Kg	6.5Kg
Material	Housing	Die casting aluminum		
	Optics	Glass		
Finish	Powder Coating			
Fixture Color	Black			
IP Rating	IP65			
Insulation class	Class I			
Mounting Option	Fixed installation			
Operating Temperature	-20°C to + 40°C			
Life Time	>36,000Hrs (Ta=30°C@L70)			
Time-Delay	10sec~10min (adjustable)			
Detection Distance	10m (Ta25°C adjustable)			
Warranty	2 Years			
Power cord	SAA certified Australian standard plug wire 3G1.0mm <sup>2</sup> *150cm			

### Highlights

- Patent design, upgrade version of classic model E023EI
- Thinner body to lower transport cost
- Free disassembly bracket for quick and easy installation
- Powered by tuya intelligence inside for smart control is optional

### Applications

- doorway &entrance
- Villa garden
- Corridor &Balcony
- Roadside