

<b>Specifications</b>					
Model No.	T033W	T033B	T033B	T033B	T033B
Led Power	20W	20W	20W	20W	20W
Install	wall mounting	40CM	60CM	80CM	1M
Solar Panel	monocrystal silicon 5V 4.5W				
LiFePO4 Battery	3.2V/6AH 18650 4*1500MA				
Charge Time	5~6hrs				
Working time	12hours				
Power Supply	SOLAR				
Input Voltage	5 VDC				
Range of Voltage	4~6 VDC				
LED	SMD2835				
LEDs Type &Qty	40pcs	40pcs	40pcs	40pcs	40pcs
Total Luminous Flux	200LM	200LM	200LM	200LM	200LM
Efficacy (±10% )	150LM/W				
Correlated Color	6500K (3000K, 4000K optional)				
Color Rendering Index	RA≥70				
Beam Angle	120°				
Product Dimension mm	237×237×80	237×237×400	237×237×600	237×237×800	237×237×1000
Luminaire Net Weight	1.2 Kg	1.76 Kg	2.1 Kg	2.44 Kg	2.78 Kg
Pcs/Carton	12Pcs	4Pcs	4Pcs	4Pcs	4Pcs
Outer Carton Size	50×50×39	50×50×48	50×50×68	50×50×88	50×50×108
Gross Weight	17.8 Kg	10 Kg	11.6Kg	13.4 Kg	14.7 Kg
Braket Color	Black				
Material	Aluminum +PC				
IP Rating	IP65				
Insulation Class	Class III				
Operating Temperature	-20°C to + 40°C				
Lifetime	>54000Hrs (Ta=30°C@L70)				
Warranty	2 Years				